S5

The S5 creates stockpiles and minimizes loader traffic, labor and fuel costs while optimizing on-site safety. It is available in diesel-hydraulic and full electric version and can be plugged in, in any other e-version crusher or screen.

6 l/h	5 l/h	2 l/h	20 kWh
Diesel-hydraulic	Diesel/electric	Electric plug-in other machinery	Electric plug-in mains

Applications

- Stockpiling
- Transport
- Loading
- Sorting
- And others

METRIC

- Tracked stacker without support legs
- Ability to stockpile, transport or load
- 75% cost saving capacity compared to loading shovel

Keestrack

TECHNICAL SPECIFICATIONS	
Capacity up to	300 t
Weight	12 t
Feed size up to	200 mm
Inclinations 9° - 22°	steps of ± 2°
Feeding chute	
Loading height	1400 - 3050 mm
Loading width (back)	1880 mm
Side loading length	2200 mm
Belt conveyor	•
Foldable main conveyor	•
Main conveyor belt (l x w)	23000 mm x 1000 mm
Discharge height (min.-max.)	6050 mm, 8200 mm, 9350 mm
Main conveyor hydraulic foldable for transport	•
Track-unit: Length, total width, track shoe width	3000, 2290, 400 mm
speed track drive	1 km/h
Engine unit(s)	30 kW @ 1500 RPM - 38kW to 42kW @ 1800 RPM
Control	Control panel & wire remote
Available drive systems	
Diesel/hydraulic drive	•
e-drive Diesel/hybrid, electric plug-in & plug-out	•
ZERO drive (no combustion engine, plug-in electric)	•

OPTIONS

Wear lining in HB450	•
Increased feeding chute	•
Additional feeding station can be applied at any position	•
Radio remote	•
Scraper at drive drum	•
Working lights	•
Several chevron belts	•

TRANSPORT	
Transport l x w x h (mm)	12000 x 2290 x 2760 mm

LEGENDA	
•	applicable - available
/	not applicable- not available

METRIC

S5

The S5 creates stockpiles and minimizes loader traffic, labor and fuel costs while optimizing on-site safety. It is available in diesel-hydraulic and full electric version and can be plugged in, in any other e-version crusher or screen.

1,58 Gal/h	1,32 Gal/h	0,52 Gal/h	20 kWh
Diesel-hydraulic	Diesel-electric	Electric plug-in other machinery	Electric plug-in mains

Applications

- Stockpiling
- Transport
- Loading
- Sorting
- And others

IMPERIAL

- Tracked stacker without support legs
- Ability to stockpile, transport or load
- 75% cost saving capacity compared to loading shovel

Keestrack

TECHNICAL SPECIFICATIONS	
Capacity up to	330 sT
Weight	13 sT
Feed size up to	7,8"
Inclinations 9° - 22°	steps of ± 2°
Feeding chute	
Loading height	4'7" - 10'
Loading width (back)	6'2"
Side loading length	7'3"
Belt conveyor	•
Foldable main conveyor	•
Main conveyor belt (l x w)	75'6" x 3'4"
Discharge height (min.-max.)	19'10", 26'10", 30'8"
Main conveyor hydraulic foldable for transport	•
Track-unit: Length, total width, track shoe width	9'10", 7'6", 1'3"
speed track drive	0,6 mph
Engine unit(s)	30 kW @ 1500 RPM - 38kW to 42kW @ 1800 RPM
Control	Control panel & wire remote
Available drive systems	
Diesel/hydraulic drive	•
e-drive Diesel/hybrid, electric plug-in & plug-out	•
ZERO drive (no combustion engine, plug-in electric)	•

OPTIONS

Wear lining in HB450	•
Increased feeding chute	•
Additional feeding station can be applied at any position	•
Radio remote	•
Scraper at drive drum	•
Working lights	•
Several chevron belts	•

TRANSPORT	
Transport l x w x h	39'4" x 7'6" x 11'1"

LEGENDA	
•	applicable - available
/	not applicable- not available

IMPERIAL